

Specialty Chemical Manufacturers for Industry, Biosecurity and Aviation

PG580

Non Water Miscible Grinding Fluid

DESCRIPTION

Non water-miscible synthetic grinding oil based on synthetic hydrocarbon.

Low viscosity, low oil misting, low foam, free of aromatic hydrocarbon.

TECHNICAL CHARACTERISTICS:

Appearance: clear, yellow liquid

Density at 15 ° C/59 ° F: 810 kg/m³

kin. Viscosity at 40 ° C/104 ° F: 6.7 mm²/s

Flash point

(COC/DIN EN ISO 2592): min. 157 ° C/315 ° F

Pour point: < -10 ° C/14 ° F

Copper Corrosion

(3 h; 100 ° C/212 ° F): 1 b - no colouration

APPLICATIONS:

The product is used undiluted and is generally applicable for grinding operations on ferrous and non-ferrous materials including tungsten carbide.

PACKAGING:

200L steel container

12 months stable if stored from 5 °C/41 °F up to 25 °C/77 °F in closed containers.

WARRANTY - All statements, information and data presented herein are believed to be accurate and reliable but are not to be taken as a guarantee, expressed or implied, for which seller assumes legal responsibility and they are offered solely for your consideration, investigation and verification. Statements or suggestions concerning possible use of this product are made without representation or warranty that any such use is free of patent infringement and are not

recommendations to infringe on any patent.

CALLINGTON HAVEN PTY LTD

Incorporated in New South Wales

ACN 000 632 404 ABN 28 000 632 404

30 South Street Rydalmere NSW 2116

PO Box 144 Rydalmere NSW BC 1701 Australia

T: (61-2) 9898 2788 F: 9684 4215

E: enquiries@calhaven.com.au W: www.callingtonhaven.com

