

ROXDIESEL ANTIFREEZE

Code 8250

FLOW IMPROVER ADDITIVE FOR DIESEL FUELS AND WINTER BLENDS IN COLD WEATHER

DESCRIPTION

Roxdiesel Antifreeze is a hydrocarbon based, ashless flow improver fuel additive which lowers the operability temperature of the fuel to sub-zero temperatures.

The Pour Point of the fuel, when treated with Roxdiesel Antifreeze is reduced from (+9°C / -9°C) to (-30°C / -40°C) depending on type and source of fuel.

Roxdiesel Antifreeze inhibits and modifies the growth of wax crystals in the fuel.

Roxdiesel Antifreeze is suitable for use in all types and speeds of mobile and stationary diesel engines.

TEST RESULTS

	<u>Pour Point</u>		
Regular Diesel Fuel	-3°C		
with Roxdiesel Antifreeze 1:500	-30°C		
with Roxdiesel Antifreeze 1:1000	-24°C		
		<u>Cloud Point</u>	<u>CFPP</u>
Winter Diesel	-9°C	-1°C	-2°C
with Roxdiesel Antifreeze 1:500	<-27°C	-1°C	-8°C
with Roxdiesel Antifreeze 1:1000	<-27°C	-1°C	-4°C

DOSAGE INSTRUCTIONS

It is important to add the Roxdiesel to the fuel when the temperature of the fuel is above its cloud point.

Dose the fuel at the fuel depot or directly into the diesel engine fuel tank.

Add the Roxdiesel to the fuel prior to topping up with the new fuel delivery. The turbulence will successfully mix the Roxdiesel through the fuel. Alternatively the Roxdiesel can be added at anytime to the fuel in storage and action of recirculating will ensure adequate dispersion.

A **dosage rate** of 1 litre of Roxdiesel to 500 litres of diesel fuel is required in the coldest areas such as the Snowy Mountains or in the New England area of NSW. A dosage of up to 1:1000 is acceptable in all other areas of Australia.

PACKAGING & AVAILABILITY

Ex-stock Sydney. Packed in 20 and 200 litre drums.

WARRANTY - All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, expressed or implied, for which seller assumes legal responsibility, and they are solely for your consideration, investigation and verification. Statements or suggestions concerning possible use of this product are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe on any patent.

16th April, 2003



CALLINGTON HAVEN PTY LTD
INCORPORATED IN NSW ACN 000 632 404 ABN 28 000 632 404
2 EUSTON STREET, RYDALMERE, NSW 2116
PO BOX 144, RYDALMERE NSW 1701 AUSTRALIA
INTERNATIONAL: (61-2) PHONE: 9898 2788 FAX: 9684 4215
EMAIL: enquiries@calhaven.com.au WEBSITE: www.callingtonhaven.com

