

# **TECHNICAL DATA SHEET**

# **ROX® PRO ENGINE FLUSH**

## Code 8290

### **DESCRIPTION**

The general use and operation of today's petrol and diesel driven engines produce by-products such as varnish, acids, resins and water. Today's engines are also designed to help protect our environment by containing pollutants that previously were released to the atmosphere, these pollutants are recirculated within the engine. Today, lubricating oils need to work harder to maintain the cleaning and suspension of all these additional contaminants. When these by-products become too concentrated to be held in suspension, deposits form on the engine's surfaces. When heat generated from the engine's normal operation combines with the deposits a sludge is formed, this sludge build-up can cause significant damage to the engine's internal surfaces. Engine flush removes contaminant deposits from the internal surfaces, which cause damage to camshafts, pistons, bearings and crankshafts. It provides a clean environment to protect new oil from immediate contamination. This prolongs the life of the detergent, anti-oxidant and dispersant additives in the new oil. The use of engine flush at every oil change will extend engine life and enhance performance.

# CAUTION NE of a factor density INCOMPRESSION OF THE STATE OF THE STA

### **FEATURES AND BENEFITS**

- Removes engine sludge
- Reduces fresh oil contaminants
- Frees sticky valves and hydraulic lifters
- Will not harm oil seals or gaskets
- Cleans the engine internally
- · Frees piston rings and restores engine compression
- Extends life of new oil
- Improves engine efficiency

### **DIRECTIONS FOR USE**

Ensure the engine is not running, add contents (300mL) to crankcase. Idle engine for 5 to 15 minutes, turn engine off and drain crankcase while oil is still hot. Replace oil plug, install new filter, and add new oil.

### PHYSICAL PROPERTIES

Appearance: Brown liquid with petroleum odour, does not mix with water.

Transparency: Clear

Density at 20oC: 0.81 ± 0.01



# **TECHNICAL DATA SHEET**

### **PACK SIZES**

300mL	8290/300
1L	8290/30
5L	8266/42
20L	8266/51

### **FIRST AID**

In case of eye contact flush thoroughly with water for at least 15 minutes. If swallowed do NOT induce vomiting. Give a glass of water to drink. If on skin, wash with soap and water. Contact a Doctor or Poisons Information Centre Australia 131 126, New Zealand 0800 764 766.

### **PRECAUTIONS & SAFETY INSTRUCTIONS**

Caution: Combustible - do not use near heat or open flame. Keep out of reach of children.

WARRANTY – All statements, information and data presented herein are believed to be accurate and reliable but are not to be taken as a guarantee, expressed or implied, for which seller assumes legal responsibility and they are offered solely for your consideration, investigation and verification. Statements or suggestions concerning possible use of this product are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe on any patent. Created 12 January 2022 Date Printed 26/07/2023 1:53 PM