

TECHNICAL DATA SHEET

ROX[®] MF 3900

Pour Point Depressant for Residual HFO

DESCRIPTION

ROX[®] MF 3900 is an ashless pour point depressant additive which improves operability for a range of MGO's and Diesel Fuel at low temperatures.

Callington pour point depressants have been used throughout the cold regions of Australia for 40 years by Oil Companies, Fuel Terminals, Vessels and end users in stationary and mobile diesel engine equipment.

HFO fuels from many different origins contain varying amounts of wax which will crystallise and gel below certain temperatures.

ROX[®] MF 3900 inhibits and modifies wax crystal growth, offering effective pour point and cold filter plugging point management for many of the currently available HFO fuels. Best results for reducing Cold Filter Plugging Point are achieved when efficient treat rates are employed.

TEST RESULTS (typical results)

MFO (380cSt)

Sample 1 Pour Point (ASTM D97)

HFO (Untreated)

+ 24°C

HFO with ROX[®] MF 3900 (1:1,000)

+ 15°C

DOSAGE INSTRUCTIONS

It is important to add the ROX[®] MF 3900 to the fuel when the temperature of the fuel is above its cloud point.

Dose the fuel at the terminal or directly into the vessel fuel tank.

Add the ROX[®] MF 3900 to the fuel prior to topping up with the new fuel delivery. The turbulence will successfully mix the ROX[®] through the fuel. Alternatively, the ROX[®] MF 3900 can be added at anytime to the fuel in storage and action of recirculating will ensure adequate dispersion.

A **dosage rate** of 1 litre ROX[®] MF 3900 to 500 litres of HFO fuel is required for the coldest climates. A dosage of up to 1:1000 is acceptable in milder temperature ranges.

FUEL ADDITIVE PARTNER

Callington is an Australian fuel additive manufacturing company, developing additives for changing fuel specifications since the early 1970's.

The advanced chemistries employed ensure the highest of performance requirements: - Asphaltene Dispersants, HFO PPD's, Tank Cleaners, Pour Point depressants, Cold Flow Improvers, Combustion Improvers, Cetane Improvers, Dispersants, Detergents, Corrosion Inhibitors, Demulsifiers, Lubricity Agents, and Antioxidants.

TECHNICAL DATA SHEET

PACKAGING & AVAILABILITY

Packed in 20 and 200 & 1000 litre containers.

WARRANTY – All statements, information and data presented herein are believed to be accurate and reliable but are not to be taken as a guarantee, expressed or implied, for which seller assumes legal responsibility and they are offered solely for your consideration, investigation and verification. Statements or suggestions concerning possible use of this product are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe on any patent.
Created 10 October 2008 Date Printed 28/03/2018 1:35 PM