

TECHNICAL DATA SHEET

ROX[®] 9300 AG

Code 8260

A Complete Diesel Fuel Treatment

DESCRIPTION

ROX[®] 9300 AG Complete Diesel Fuel Treatment is a multi-functional diesel fuel maintenance product. It is specially designed to give an overall improvement on most aspects of fuel efficiency. It provides several benefits to users as follows:

Injector Cleanliness	Improved Exhaust Emission	Powerful Biocide
Improved Lubricity	Enhances Fuel Stability	Enhances Demulsibility
Improves Fuel Economy		

APPLICATION

The recommended treat rate is 1:500 for the initial first time treatment and 1:1000 to 1:2000 for subsequent treatments.

Add 1 part of ROX[®] 9300 AG to 500 parts of Diesel for the first treatment. Mix well.

For subsequent treatment add 1 part to 1000 parts of Diesel.

SPECIFICATION

Appearance colour	:	light brown coloured liquid
Density	:	0.82 +/- 0.02
Transparency	:	clear

HANDLING

Combustible - Do not use near open flame or heat. Keep out of reach of children. Refer to the Material Safety Data Sheet for further information.

FIRST AID

If swallowed - do NOT induce vomiting. Give a glass of water to drink. Contact a Doctor or Poisons Information Centre. If in eyes flush with plenty of water for at least 15 minutes. If on skin, wash with soap and water.

PACKAGING

Available in 5 litre, 20 litre and 200 litre containers.

WARRANTY – All statements, information and data presented herein are believed to be accurate and reliable but are not to be taken as a guarantee, expressed or implied, for which seller assumes legal responsibility and they are offered solely for your consideration, investigation and verification. Statements or suggestions concerning possible use of this product are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe on any patent.

Created 10 October 2008 Date Printed 28/03/2018 9:21 PM