

TECHNICAL DATA SHEET

WOODSTRIP

For The Furniture Restoration Industry

Code 6004

DESCRIPTION

Woodstrip paint stripper is a solvent based, non-caustic, heavy bodied paint remover. It is carefully formulated for the furniture restoration industry to avoid discoloration and darkening to delicate timbers. It contains evaporation retarders and thickeners.

Its primary use is for the professional renovation of antique and old furniture pieces, doors, window frames, architraves, skirting boards and all building joinery.

Method of Use

1. Open Woodstrip paint stripper can slowly to avoid sudden pressure release.
2. If the painted surface is oily or soiled, wash down with a degreasing solution or with warm water with dishwashing detergent.
3. Carefully pour a working quantity of Woodstrip paint stripper into an open top container.
4. With a soft brush, apply a generous, thick coat of Woodstrip paint stripper to the surface to be stripped. Cover only enough area that can be scraped off before the Paint Stripper dries.
5. Wait for paint to wrinkle, blister or soften. This should take from 1 to 15 minutes depending on the type and age of the paint.
6. Remove the paint with a suitable paint scraper. Check with your hardware for the best type of scraper as care taken with the choice of scraper can save a lot of time and prevent possible damage to timber.

If all the paint is not removed with the first application, then apply a second coat of Woodstrip paint stripper.

7. Once most of the paint has been scraped off, rub timber surfaces down with dry steel wool and metal surfaces with steel wool or scouring pads. This process should remove small bits of paint left on the surface. Wear gloves.
8. Finally, wash down and clean the surface. Using a scouring pad or steel wool, wash down with water or Methylated Spirits. If it is intended that the timber be finished off with sanding, use hot water with laundry powder to effectively and thoroughly wash down the surface.
9. Allow surface to dry. Surface is now ready for repainting or for sanding.

... /2

TECHNICAL DATA SHEET

Woodstrip (6004) - Page 2 of 2

PROPERTIES

Woodstrip is not corrosive to most materials. It may have degrading effects on rubber, perspex some plastics and composites.

Appearance	: Clear viscous liquid
Odour	: Ammoniated
Specific Gravity	: 1.18
Shelf Life	: Up to 12 months
Storage	: Store in a cool place and out of direct sunlight
U.N. No.	: 2810
Class	: 6.1
Packing Group	: III

WARNING

Prolonged exposure to vapour is harmful to health. Use in well ventilated areas. Forms dangerous gas near radiators or naked flames.

FIRST AID

If poisoning occurs contact a doctor or Poisons Information Centre. If swallowed do not induce vomiting. Give a glass of water. Avoid giving milk oils and alcohol. If skin contact occurs remove contaminated clothing and wash skin thoroughly. Remove from contaminated area. Apply artificial respiration if not breathing. If in eyes, hold eyes open and flood with water for at least 15 minutes and see a doctor as soon as possible.

SAFETY PRECAUTIONS

Woodstrip contains Dichloromethane. Do not smoke while using Woodstrip. Avoid contact with the eyes. Wear protective gloves, goggles and clothing. Avoid breathing its vapours. Use good ventilation in working area.

WARRANTY – All statements, information and data presented herein are believed to be accurate and reliable but are not to be taken as a guarantee, expressed or implied, for which seller assumes legal responsibility and they are offered solely for your consideration, investigation and verification. Statements or suggestions concerning possible use of this product are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe on any patent.

Created 27 October 2010 Date Printed 5/04/2018 5:29 PM